



Mühendislik Ltd. Şti.
Ledli Aydınlatma

● **Product Picture**



● **Features**

1. Emitted Color: Pure White, Warm White.
2. Lens Appearance: Water Clear.
3. The angle of Lens can be choosed.
15° 30° 45° 60°.
4. Material of crust: Aluminum hull
5. Protection category: IP65.
6. Projection Distance: 6-12M.
7. Weight: 3.2KG.
8. RoHS Compliant: RoHS
9. Choices of luminous intensities for indoor and outdoor application.
10. High reliability and long life

● **Absolute Maximum Ratings**

Parameter /项目	Symbol	Rating			Unit
		Min.	Typ.	Max.	
Input Voltage AC	Vin	90	230	240	V
AC Frequency	F	-	50	-	Hz
Input Current AC	I(rms)	0.358	0.37	0.841	A
Operating Tem	Ta	-25	25	50	°C
Operating Hum	Ha	5%-95%(No Water.			-
Storage Tem	Ts	-35~60			°C

● **Electrical and optical characteristics (Ta=25°C)**

Parameter	Condition	Symbol	Min.	Typ.	Max.	Unit
Power Dissipation	Vin=230V~,50Hz	Pd	45.1	45.25	47.2	W
Luminous Flux	Vin=230V~,50Hz	IV(P)	1600	1950	2300	Lm
		IV(W)	1300	1650	1750	Lm
Color Temperature	Vin=230V~,50Hz	C.T.(P)	4000	6000	8000	K
		C.T.(W)	3000	3500	4000	K